

Particleboard Core Non-Rated & 20 Min / Non-Bonded Construction

Commercial Series – Wood Veneer Doors
Cendura™ by Masonite Architectural™

	PRODUCT SPECIFICATIONS	INTERIOR USE ONLY			
DIMENSIONS	Thickness	1-3/4", 1-3/8" (NR only)			
	Maximum Size	ITS-WH AND UL			
			Non-Rated	20-Min Fire-rated Neutral Pressure	20-Min Fire-rated Cat B Positive Pressure
		Singles	4'0" x 8'0"	4'0" x 8'0"	4'0" x 8'0"
Pairs	8'0" x 8'0"	8'0" x 8'0"	8'0" x 8'0"		
	Prefit Size (Default)	Singles: beveled 2 edges, 7/32" width and 7/8" height Pairs: beveled 2 edges, 3/16" width and 7/8" height 1-3/8" Thick Doors: consult factory for specific prefit and bevel options			
CONSTRUCTION	Surface Material	Wood Veneers: WDMA A/B-Grade 1/50" nominal thickness: - Uniform Lite Birch: B-grade Rotary Cut, book and running match - Natural Birch: A-grade Rotary Cut or Plain Sliced, book and running match			
	Crossbands	One Piece High Density Fiberboard (HDF)			
	Vertical Edges	Compatible Edges: - Uniform Lite Birch: Mill Option Hardwood w/ Structural Composite Lumber Backer (1-1/4" before trim) - Natural Birch: Full Length Softwood Stiles (1-1/4" before trim)			
	Horizontal Edges	Mill Option: Structural Composite Lumber or Softwood (1-1/4" before trim)			
	Face & Core Assembly Adhesive	Type 1			
	Core Construction	Wood-based Particleboard Core			
	Lite Openings / Louvers	- Factory glazing recommended - Available with wood beads, metal vision frames, wood wrapped metal vision frames, or applied grilles - Wood and metal louvers in non-rated doors			
	Distance from Lock & Lite Cutouts	3-1/4" minimum distance from adjacent lock and lite cutouts			
	Details	Standard and custom applied moulding profiles, reveals and divided lites upon request			
	Machining	Machining preparation per hardware manufacturer's templates			
	Factory Finish	Clear, standard and custom stain colors			
CREDITS & STANDARDS	Environmental Standards	CARB PH2			
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard Construction)			
	WDMA Performance Duty Level	N/A			
WT.	Door Weight	Average: 5.3 lbs/sf			
	Warranty	Limited Lifetime. No exterior warranty. Interior use only.			