

Hollow Core

Economy Series - Wood Veneer Doors

	PRODUCT SPECIFICATIONS	INTERIOR USE ONLY
DIMENSIONS	Thickness	1-3/4", 1-3/8"
	Maximum Size	Non-Rated
		Singles
Bifolds		6'0" x 7'0" (4-door)
	Prefit Size (Default)	1-3/4" Thick Doors: beveled 2 edges, 7/32" width and full height 1-3/8" Thick Doors: square edges, full size
CONSTRUCTION	Surface Material	Wood Veneers: Thin Face and Select Grade, book and running match Species: Rotary Natural Birch and Plain Sliced Red Oak
	Crossbands	One Piece Medium Density Fiberboard (MDF)
	Vertical Edges	Mill Option: Full Length Softwood Stiles (1-1/4" before trim), typical Red Oak veneer edge band applied to 1-3/4" thick Red Oak doors
	Horizontal Edges	Mill Option: Softwood Rails (2-1/2" before trim), typical
	Face & Core Assembly Adhesive	Type 2
	Core Construction	5-1/2" Kraft Paper Honeycomb Lock blocks (2) per door
	Lite Openings / Louvers	No Lites / No Louvers
	Distance from Lock & Lite Cutouts	N/A
	Details	N/A
	Machining	Machining preparation per hardware manufacturer's templates Some limitations apply
	Factory Finish	- Clear - Standard and custom stain colors not recommended; limited availability
	CREDITS & STANDARDS	Environmental Standards
Quality Standards		Manufacturer's Internal Quality Standards
WDMA Performance Duty Level		N/A
WT.	Door Weight	Average: 1.7 lbs/sf
	Warranty	Limited One Year. No exterior warranty. Interior use only.