

Particleboard Core Non-Rated & 20 Min / Non-Bonded Construction

Economy Series – Wood Veneer Doors

	PRODUCT SPECIFICATIONS	INTERIOR USE ONLY																			
DIMENSIONS	Thickness	1-3/4"																			
	Maximum Size	Sizes noted in this table are specific to 1-3/4" doors. <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th colspan="3">ITS-WH AND UL</th> </tr> <tr> <th></th> <th>Non-Rated</th> <th>20 Min Fire-rated Neutral Pressure</th> <th>20 Min Fire-rated Cat B Positive Pressure</th> </tr> </thead> <tbody> <tr> <td>Singles</td> <td>3'0" x 8'0"</td> <td>3'0" x 8'0"</td> <td>3'0" x 8'0"</td> </tr> <tr> <td>Pairs*</td> <td>6'0" x 8'0"</td> <td>6'0" x 8'0"</td> <td>6'0" x 8'0"</td> </tr> </tbody> </table>					ITS-WH AND UL				Non-Rated	20 Min Fire-rated Neutral Pressure	20 Min Fire-rated Cat B Positive Pressure	Singles	3'0" x 8'0"	3'0" x 8'0"	3'0" x 8'0"	Pairs*	6'0" x 8'0"	6'0" x 8'0"	6'0" x 8'0"
			ITS-WH AND UL																		
			Non-Rated	20 Min Fire-rated Neutral Pressure	20 Min Fire-rated Cat B Positive Pressure																
Singles	3'0" x 8'0"	3'0" x 8'0"	3'0" x 8'0"																		
Pairs*	6'0" x 8'0"	6'0" x 8'0"	6'0" x 8'0"																		
* Not factory matched																					
	Prefit Size (Default)	1-3/4" Thick Doors: beveled 2 edges, 7/32" width and 7/8" height																			
CONSTRUCTION	Surface Material	Wood Veneers: Thin Face & Select Grade, Book and Running Match Species: Rotary Natural Birch and Plain Sliced Red Oak																			
	Crossbands	One Piece Medium Density Fiberboard (MDF)																			
	Vertical Edges	Mill Option: Full Length Softwood Stiles (1-1/4" before trim), typical Red Oak veneer edge band applied to 1-3/4" thick Red Oak doors, typical																			
	Horizontal Edges	Mill Option: Softwood Rails (1-1/4" before trim), typical																			
	Face & Core Assembly Adhesive	Type 2																			
	Core Construction	Wood-based Particleboard Core																			
	Lite Openings / Louvers	<ul style="list-style-type: none"> - Factory glazing recommended - Available with wood beads, metal vision frames - Wood and metal louvers in non-rated doors 																			
	Distance from Lock & Lite Cutouts	3-1/4" minimum distance from adjacent lock and lite cutouts																			
	Machining	Machining preparation per hardware manufacturer's template Some limitations apply																			
CREDITS & STANDARDS	Factory Finish	<ul style="list-style-type: none"> - Clear - Standard and custom stain colors not recommended; limited availability 																			
	Environmental Standards	CARB PH2																			
	Quality Standards	Manufacturer's Internal Quality Standards																			
	WDMA Performance Duty Level	N/A																			
WT.	Door Weight	Average: 4.3 lbs/sf																			
	Warranty	Limited One Year. No exterior warranty. Interior use only.																			