

Architectural Series – Hollow Metal Doors

Polystyrene Core

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS		
DESCRIPTION	Thickness	1-3/4"
	Label Capabilities	ITS-WH (fire rated up to 3 hours) , Mylar Label
	Prefit Size (default)	Beveled 2 edges, handed and undersized 1/4" width and 7/8" height
	Surface material	18-Gauge A60 Galvanneal Steel
CONSTRUCTION	Thermal Insulation (R-Value)	6.6
	Vertical Edges	Seamless Lockseam design; prepped for common hinge and lock locations
	Horizontal Edges	Top & Bottom: Inverted continuous channel; welded to face. Flush Top Cap installed.
	Hinge reinforcement	7-Gauge steel hinge reinforcement projection welded on each end to edge
	Core construction	Polystyrene core
	Lite openings / Louvers	<ul style="list-style-type: none"> - Factory glazing recommended - Available metal vision frames - Metal louvers in non-rated/rated doors
	Lock & lite cutouts	Standard locations recommended; custom locations available
	Machining	Additional machining preps and modifications per hardware manufacturer's template; Some limitations apply.
	Factory finish	Gray Water-based Primer
	Quality Standards	HMMA 841-13; SDI-100, Level 2, Model 2
WT.	Door Weight	5.7 lbs / square feet
	Warranty Limited	Limited Lifetime Warranty