

## Commercial Series - Hollow Metal Doors

### Polystyrene Core

#### PRODUCT SPECIFICATIONS

| DESCRIPTION  | Thickness                    | 1-3/4"   |
|--------------|------------------------------|--|
|              | Label Capabilities           | ITS-WH ( fire rated up-to 3 hours ) , Mylar Label  |
|              | Prefit Size                  | Square 2 edges, non-handed and undersized 1/4" width and 7/8" height   |
|              | Surface material             | 18-Gauge A60 Galvanneal Steel  |
| CONSTRUCTION | Thermal Insulation (R-Value) | 6.6  |
|              | Vertical Edges               | Lockseam design; prepped for common hinge and lock locations   |
|              | Horizontal Edges             | Top & Bottom: Inverted continuous channel; welded to face. Flush Top Cap installed.  |
|              | Hinge reinforcement          | 7-Gauge steel hinge reinforcement projection welded on each end to edge  |
|              | Core construction            | Polystyrene core   |
|              | Lite openings / Louvers      | <ul style="list-style-type: none"> <li>- Factory glazing recommended</li> <li>- Available metal vision frames</li> <li>- Metal louvers in non-rated/rated doors</li> </ul> |
|              | Lock & lite cutouts          | Standard locations recommended; custom locations available   |
|              | Machining                    | Additional machining preps and modifications per hardware manufacturer's template;Some limitations apply.  |
|              | Factory finish               | Gray Water-based Primer  |
|              | Quality Standards            | HMMA 841-13; SDI-100, Level 2, Model 1   |
| WT.          | Door Weight                  | 5.7 lbs / square feet  |
|              | Warranty Limited             | Limited Lifetime Warranty  |